

## **Opacity Charts**

# Opacity Charts (Half black and half white) 250x140mm; Film-laminated (500 pcs/package)

**BGD 1101** 

## **Product Description**

Solvica offers a wide range of drawdown cards and charts for virtually any application and coating material. Stringent quality control during the production process ensures that they have the most consistent color and gloss in the industry. Test charts are easy to use and provide an economical substrate to test a variety of coating properties, such as opacity, spreading rate, and flow & leveling behavior. They are used for testing architectural, industrial, automotive, wood finishes, or even cosmetic products (e.g., nail polish). Depending on the material properties of the product to be tested and its usage, different types of drawdown cards are available.



#### **Standards**

ASTM D 344



## **Opacity Charts**

# Opacity Charts (Half black and half white) 250x140mm; Film-laminated (500 pcs/package)

#### **BGD 1101**

#### **Technical Specification**

Depending on the types of solvent used in paint formulations, a drawdown chart needs to be more or less solvent-resistant. The resin type requires different solvent types, and depending on the polarity of the solvent, the organic ingredients will be more or less activated. Therefore, Solvica offers two types of drawdown cards and charts.

#### Clear-coated Charts

- Ideal for a wide range of coating systems: water- and solvent-borne technologies
- Guaranteed non-fluorescent paper in compliance with ASTM D 344
- Repeatable color and gloss, lot after lot
- Superior adhesion characteristics, especially with latex paints
- Rugged design (0.5 mm thickness) to prevent warping and bending after the coating is applied
- Package is shrink-wrapped with low permeability plastic to prevent moisture absorption during shipping and storage Film

#### Laminated Charts

- Excellent solvent resistance
- Repeatable color and gloss, lot after lot
- Smooth, structure-free surface
- Superior adhesion properties and flexibility
- 0.5 mm thickness
- Double film laminated; will not warp and bend even in high humidity environments



## **Opacity Charts**

## Opacity Charts (Half black and half white) 250x140mm; Film-laminated (500 pcs/package)

**BGD 1101** 

**Main Technical Parameters** 

Film-laminated product (whether in this sheet or otherwise) is correct we have no control over either the product. Therefore, unless we specifically agree in writing to do so, lability whatsoever or howsoever arising for the performance of the product or on the product. Therefore, unless we specifically agree in writing to do so, lability whatsoever or howsoever arising for the performance of the product or on the product. The product or personal for the performance of the product or on the performance of the product or for any loss or decorated by the product. The product of the performance of the product or for any loss or decorated by the product. The performance of the performance of the product or for any loss or decorated by the product. The product or for any loss or decorated by the product or for any loss or decorated by the product. The performance of the product or for any loss or decorated by the product or for any loss or decorated by the product of the product. The product of the performance of the product or for any loss or decorated by the product of the product of the product. The product of the pro