

Ford Flow Cup #3

BGD 125-3

Product Description

Ford Cups produced by our supplier are in accordance with International Standard ASTM D1200, D333, and D365. For easy measurement of the viscosity of paints, inks, lacquers and other liquids.

All our Ford cups are machined anodic oxidation aluminum with removable stainless steel orifice and are guaranteed to be within 2% throughout the recommended range of use.



Standards

- ASTM D1200
- D333
- D365

Technical Specification

- Internal Diameter $50 \pm 0.05 \text{ mm}$
- Outer Diameter $86 \pm 0.1 \text{ mm}$
- Internal Orifice Length $10 \pm 0.1 \text{ mm}$
- Production Tolerance $\pm 2\%$
- Supplied with calibration certificate

Ford Flow Cup #3

BGD 125-3

Main Technical Parameters

Ford Cup Details	Ford Cup (2#)	Ford Cup (3#)	Ford Cup (4#)	Ford Cup (5#)	Ford Cup (4#) Hand-Held
Internal Vertical Height	43±0.1mm	43±0.1mm	43±0.1mm	43±0.1mm	43±0.1mm
Internal Orifice ϕ mm	2.53 mm	3.40 mm	4.10 mm	5.20 mm	4.10 mm
External Orifice ϕ mm	5.0±0.5mm	5.5±0.5mm	6.0±0.5mm	7.6±0.5mm	6.0±0.5mm
Centistokes Range	25-120	49-220	70-370	215-1413	70-370
Efflux Time sec ± 0.2	40-100	25-105	20-105	20-105	20-105
Ordering Information	BGD 125/2	BGD 125/3	BGD 125/4	BGD 125/5	BGD 125/4P

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development