

DIN Flow Cup

DIN Flow Cup #4 Orifice Ø 4.0 mm (DIN 53211)

BGD 127-4

Product Description

Our DIN and Dip Viscosity Cups are produced with an easily removable orifice. Cup and orifice production tolerance permits replacement of the orifice without loss of acceptable tolerance.

In accordance with Deutsche Norm DIN 53211

Can be used for measuring low viscosity coatings and inks during production and application.



Technical Specification

Volume of Cup: 100 ±1 ml

Orifice Diameter: 4 mm ± 0.02 mm
Body made of anodized aluminium

- Stainless steel orifice, interior polished
- Calibration certificate included

Standards

DIN 53211



DIN Flow Cup

DIN Flow Cup #4 Orifice Ø 4.0 mm (DIN 53211)

BGD 127-4

Main Technical Parameters

DIN Cup Details	DIN Cup (#2)	DIN Cup (#4)	DIN Cup (#6)	DIN Cup (#8)	DIN Cup (#4) Hand-Held
Volume of Cup	100 ±1 ml				
Orifice Ø (mm)	2.0±0.02mm	4.0±0.02mm	6.0±0.02mm	8.0±0.02mm	4.0±0.02mm
Ordering Information	BGD 127/2	BGD 127/4	BGD 127/6	BGD 127/8	BGD 127/4P

^{*} DIN Flow Cup Nozzles: BGD 1272

Accessoires

- BGD 130 Stand for Flow Cups (ISO, DIN & Ford)
- SLV-RF-SW-110 Renkforce RF-SW-110 Digital stopwatch

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development