

3M Epoxy Adhesive (Scotch-Weld DP410)

BGD 1527

Product Description

3M™ Scotch-Weld™ Epoxy Adhesive 410 is a two-part structural adhesive. It is designed for use where toughness, high strength and rapid cure are required. It is fast setting and a high performance adhesive. It is tough with excellent durability. Get strong, tough and fast drying adhesion with 3M™ Scotch-Weld™ Epoxy Adhesive 410. Our high performance, long-lasting adhesive sets quickly at room temperature and faster when mild heat is applied. Mix and apply our adhesive with ease. It comes in a handy 2:1 mix ratio by volume, that's low flow for easy use. It's a toughened epoxy system with good elevated temperature and environmental resistance.



Technical Specification

- Applications: Aluminum bonding, Composite Bonding, Impact Resistant, Metal Bonding, Small Joint Assembly, Structural Bonding
- Rapid cure at room temperature; cure rate may be accelerated by the application of mild heat
- Toughened epoxy system with good elevated temperature resistance
- Convenient 2:1 mix ratio by volume
- Good environmental resistance
- Mixed adhesive is low flow for ease of application

3M Epoxy Adhesive (Scotch-Weld DP410)

BGD 1527

Main Technical Parameters

- Container Size (Metric): 50 ml
 - Container Size (Imperial): 1.691 fl oz (US)
 - MSDS available upon request
-
- Ordering information: BGD 1527 - Scotch-Weld Epoxy Adhesive DP410
 - Accessory: 3M EPXN48 Mixing: Nozzle Designed for use with 1:1 and 2:1 48.5/50mL 3M™ Scotch-Weld™ Structural Adhesive Duo-Pak Cartridges.

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development