

Multifunction Stormer Krebs viscometer 40.2KU - 141 KU

BGD 187

Product Description

BGD 187 Multifunction Stormer Viscometer is designed in accordance with ASTM D 562. It is fully upgraded from BGD186, with more reasonable structure, simpler operation and wider application.

Features

- Apply a new structural design: it can be split into portable viscometer directly, and able to meet the test requirements for production site or other various temporary application environment.
- Apply a new appearance design using 7 inch industrial grade full touch screen, more clearly display and more convenient operation.
- Apply new lift structure design: no need handle, reduce the overall space.
- Supplied with calibration certificate
- Built-in infrared thermometer sensor to measure sample temperature, more convenient and more precise.
- Magnetic rotor enables rapid installing, dismantlement or cleaning.
- Designed with calibration function: the end-user can calibrate regularly with standard oil, no need return to the manufacturer. Significant costsavings.



Standards

ASTM D 562

Multifunction Stormer Krebs viscometer 40.2KU - 141 KU

BGD 187

Main Technical Parameters

- Range: 40.2KU 141.0 KU (27-5250 CP)
- Accuracy: $\pm 1.5\%$ of full scale range
- Repeatability: $\pm 1\%$ of full scale range
- Paddle Speed: 200r/min ± 0.5 r/min
- Volume of container: 500ml
- Power Supply 220V 50Hz
- Overall Dimensions 230 mm \times 180 mm \times 465 mm(L \times W \times H)
- Weight 3 KG
- Ordering Information BGD187 - Multifunction Stormer viscometer

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development