

# Two-sided applicator: width 80mm, wft 25-50 µm

**BGD 202-1**

## Product Description

---

The U shaped-Type Two-Sided Applicator is made using modern technology of metallurgy with a precision grinding machine. The accuracy of the Gap Depth is  $\pm 1.0\mu\text{m}$  (50µm and below) and or 2% of Full Scale. It is designed with ASTM D 823-25

It is made of high-grade, corrosion-resistant stainless steel 440C.



## Technical Specification

---

- Wet Film Width: 80mm
- Total length: 100mm

## **Two-sided applicator: width 80mm, wft 25-50 µm**

### **BGD 202-1**

#### **Main Technical Parameters**

---

##### **Ordering information**

BGD 202/1 25µm 50µm

BGD 202/2 75µm 100µm

BGD 202/3 150µm 200µm

BGD 202/4 300µm 400µm

##### **Disclaimer**

---

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development