

Four-sided frame applicator: 80mm, wft 50-100-150-200µm

BGD 204-3

Product Description

The Frame-Type Four-Sided Applicators are designed to produce uniform films of paint, adhesives, and similar products on flat substrates. They combine the precision of fixed applicators with the flexibility of multiple gap options in one unit. These applicators are suitable for use with aqueous, acidic, and alkaline products. They are crafted from high-grade, corrosionresistant stainless steel 440C.



Technical Specification

- Frame width: 100 mm
- Wet film width: 80 mm
- $^{\bullet}$ Wet film thickness: 50-100-150-200 μm



Four-sided frame applicator: 80mm, wft 50-100-150-

200µm

BGD 204-3

Main Technical Parameters

Model	Wet Film Thickness
BGD 204-1	5-10-15-20 μm
BGD 204-2	25-50-75-100 μm
BGD 204-3	50-100-150-200 μm
BGD 204-4	30-60-90-120 μm

Ordering information: BGD 204-3 four-sided frame applicator: 80mm, wft 50-100-150-200 μm

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development