

Four-sided applicator: 160mm, wft 30-60-90-120 µm

BGD 205-4

Product Description

A flexible and easy to use applicator, combining 4 gaps sizes in one unit. The cylindrical shape provides excellent results particularly on firm, smooth surfaces. By simply rotating through 90° angles, the next gap size is placed onto the substrate. It is designed according to ASTM D 823-25 and made of high-grade, corrosion-resistant stainless steel 440C.



Technical Specification

- Film width: 160mm
- Wet film thickness: 30-60-90-120 µm

Four-sided applicator: 160mm, wft 30-60-90-120 µm**BGD 205-4****Main Technical Parameters**

LONG TYPE	Wet Film Thickness (µm)
Wet Film Width: 160 mm	
Total Length: 190 mm	
BGD 205/2	25, 50, 75, 100
BGD 205/3	50, 100, 150, 200
BGD 205/4	30, 60, 90, 120
BGD 205/5	100, 200, 300, 400
BGD 205/6	50, 75, 100, 150
BGD 205/7	100, 150, 200, 250
BGD 205/8	250, 500, 750, 1000

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development