


# Eight-sided applicator: 80mm, wft 25-50-75-100-150-200-300-400µm

**BGD 207-2**

### Product Description

---

A flexible and easy to use applicator, combining 8 gaps sizes in one unit. The octagonal shape provides excellent results particularly on firm, smooth surfaces. By simply rotating through 90° angles, the next gap size is placed onto the substrate. It is designed according to ASTM D 823 and made of high-grade, corrosion-resistant stainless steel 440C.



### Standards

---

ASTM D 823

### Technical Specification

---

- Wet Film Width: 80 mm
- Wet Film Thickness: 25-50-75-100-150-200-300-400µm
- Material: corrosion-resistant stainless steel 440C

**Eight-sided applicator: 80mm, wft 25-50-75-100-150-  
200-300-400µm**

**BGD 207-2**

**Main Technical Parameters**

---

**Ordering information:** BGD 207-2

**Disclaimer**

---

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development