

Pen Portable pH Meter (-1.00~15.00pH) / 0.01pH

BGD 288

Product Description

BGD 288 Pen Portable pH Meter 1.00~15.0 / 0.1pH

It is designed like a pen and more convenient to use anywhere and anytime!

Features: automatic calibration, automatic temperature compensation, automatic power off, low voltage alarm, pH electrode invalidation display, etc.

Easy to use: single button operation.

Reliable structure design: meets IP57 waterproof standard, replaceable batteries, supplied with calibration solution, electrode soaking solution and standby batteries in a portable case.



Standards

IP 57 waterproof

Technical Specification

- Measuring range: -1.00~15.00 pH
- Resolution: 0.01 pH
- Accuracy: ± 0.01 pH
- Stability: ± 0.01 pH/3h
- Temperature compensation range: 0~60C (automatic)
- Shows Temperature: Yes
- Automatic Calibration: 1 ~ 3 points (pH4.00/7.00/10.01)
- Power: CR2032 lithium batteries (2 pcs) continuous use for over 100 hours
- Dimensions: 148×29×14mm
- Weight: 43g

Pen Portable pH Meter (-1.00~15.00pH) / 0.01pH

BGD 288

Main Technical Parameters

Ordering Information: BGD 288

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development