

Cutters for BGD 502 Cross Hatch Adhesion Testers

BGD 502 - cutters

Product Description

The Solvica BGD 502 Cross Hatch Adhesion Tester Series are widely used to evaluate the adhesion of various coatings. A high-precision machined wheel featuring 6 or 11 cutting blades with different spacings is mounted in a comfortable wooden handle.

The test is performed by making two series of crossed cuts at right angles. The resulting lattice is then brushed or cleared with adhesive tape. Depending on the coating thickness and the corresponding spacing, results can be classified according to a standard scale. The tool is durable and long-lasting, offering 8 cutting edges that can be rotated when worn.



When applied to multi-coat systems, the tester allows for the assessment of the resistance to separation between individual coating layers.

Furthermore, Solvica cross hatch testers are designed with either a standard rake-type holder (BGD 502) or a special turnable cutter holder (BGD 504), convenient for cutting coatings on curved or uneven surfaces and ensuring uniform pressure through to the substrate.

Standards

ISO 2409; ISO 16276-2; ASTM D3359; ASTM D3302; BS 3900 E6

Technical Specification

Accessory for BGD 502 Cross Hatch Adhesion Testers

Cutters for BGD 502 Cross Hatch Adhesion Testers

BGD 502 - cutters

Main Technical Parameters

Ordering Information	No. Of Teeth	No. Of Cutting Edges	Cutter Spacing
BGD 502/J-002	11	8	1mm
BGD 502/J-003	6	8	1mm
BGD 502/J-004	11	8	2mm
BGD 502/J-005	6	8	2mm
BGD 502/J-006	6	8	3mm

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development