

Cross Hatch Tester

BGD 502-series

Product Description

This BGD 502 Cross Hatch Adhesion Tester series is widely used to evaluate the adhesion of various coatings. A high precise machined wheel presenting 6 or 11 cutting blades with various spacing is mounted in a handle.

The test is carried out by performing 2 series of crossed cuts at right angle. The obtained lattices is either brushed or cleared with adhesion tape. According to the coatings thickness and the related spacing, the results can be classified with reference to a standard scale. It has long life tool with 6 cutting edges and comfortable wood handle.

When applied to multi-coat system, assessment of the resistance to separation of individual layers of the coating from each other may be made.



Standards

BS 3900 E6 BS/EN ISO 2409 ASTM D 3359 D 3302

Technical Specification

Cross Hatch Tester

BGD 502-series

Six or eight working side blades: When the blade edge is not sharp enough, users can loosen the boat-type nut and top thrust screw to rotate it to select a new blade.

Multi-cutting blades spacing: 1mm / 2mm / 3mm

The number of square 25 squares / 100 squares

Normal Packing List

- Carrying case
- Cross Hatch Cutter & Handle
- 1 roll of 3M Scotch Transparent Tape
- Brush
- Magnifier
- Calibration Certificate

Cross Hatch Tester

BGD 502-series

Main Technical Parameters

Ordering Information	No. Of Teeth	No. Of Cutting Edges	Cutter Spacing
BGD 502/2A	11	8	1mm
BGD 502/3A	6	8	1mm
BGD 502/4	11	6	2mm
BGD 502/5A	6	8	2mm
BGD 502/6A	6	8	3mm

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development