

Wet Abrasion Scrub Tester (ISO 11998)

BGD 526-2

Product Description

Paint often becomes soiled especially near doorways, windows, and in work and play areas. Coated surfaces need to be tested for resistance to abrasion caused by a brush, sponge, or other means. The Wet Abrasion Scrub Tester can produce a repeatable, controlled condition to simulate everyday use or wear patterns.

BGD 526-2 Wet Abrasion Scrub Tester can examine washability and related properties that affect the stain resistance of coatings. Detergent performance testing can also be determined in a reproducible manner.

In accordance with standard EN ISO 11998.

- Running speed can be set to meet requirements of different standards.
- With four-digit counter, start the machine and it will automatically be stopped when reaching set times.
- Compatible with abrasion pads to comply with different standard EN ISO 11998. (See ordering information for all other standards).
- Quickly and easily to load and unload testing samples and replacing abrasion head.
- Can work normally under different voltages and frequencies
- With stable and uniform running speed because of Push-rod design
- Features two brush holders for side-by-side testing
- Long service life with hard and durable design
- The whole machine body is made of anodized aluminum, having stable working status, repeatable test results - no exception - even in the fastest speed of the stroke.
- BGD 526-2 does not include a peristaltic pump design (available on all models, except BGD 526-2), for accurate flow of control scrub medium. All other models in the BGD 526-series, as well as BGD 527 (in accordance with EN ISO 11998 & ASTM D 2486) and BGD 528 ('multi-standard') will be supplied with such a peristaltic pump.



Wet Abrasion Scrub Tester (ISO 11998)

BGD 526-2

Standards

EN ISO 11998

Technical Specification

- Stroke Length: 300 mm
- Weight of brush (including device holding brush): 135±1g (ISO 11998)
- Frequency of travel: 5~95 times/min (adjustable)
- Range of count: 0~9,999 times
- Size of test plate: 430×150×0.03mm
- Power of motor: 25W
- Power: 110V~220V ; 50/60 Hz
- Overall size: 500x460x280 mm
- Capacity of Water Container: 1L

Wet Abrasion Scrub Tester (ISO 11998)

BGD 526-2

Main Technical Parameters

Ordering Information:

- BGD 526/1 - Wet Abrasion Scrub Tester (ASTM D 2486)
- **BGD 526/2 - Wet Abrasion Scrub Tester (ISO 11998, does not include peristaltic pump)**
- BGD 526/3 - Wet Abrasion Scrub Tester (ASTM D 3450)
- BGD 526/4 - Wet Abrasion Scrub Tester (ASTM D 4213)
- BGD 526/5 - Wet Abrasion Scrub Tester (ASTM D 4828)
- BGD 526/6 - Wet Abrasion Scrub Tester (DIN 53778)
- BGD 527 - Wet Abrasion Scrub Tester (ASTM D 2486 & ISO 11998)

Accessoires

- BGD 1045 - Abrasive Pad 3M Scotch Brite (ISO 11998 - 90x39mm - pack of 100)
- BGD 1185 - Abrasion Heads for ISO 11998 (3M Scotch Brite handpads + Weights, total 135±1g)
- BGD 2208 - Black Plastic Panel (432x165x0.25mm) - pack of 100 units

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development