

Wet Film Comb Thickness Gauges - stainless steel

BGD 531-Series

Product Description

BGD 531 series Wet Film Thickness Gauges

The Wet Film Comb Thickness Gauges are made of a comb-shaped design with precision cut gaps to determine the coating thickness by placing vertically onto a wet coated substrate. It is a corrosion-resistant stainless steel with a hole at the top corner so that a string (not included) can be attached for hooking.



Technical Specification

All Wet Film Thickness Comb Gauges are machined by high precision CNC and with less than 3 micron deviation. They come standard with 10 gaps with inscriptions of the thickness at the side of each gap. It is recommended to replace a new gauge if there are chips, crack or uneven at the gap(s) on the gauge.

Wet Film Comb Thickness Gauges - stainless steel

BGD 531-Series

Main Technical Parameters

Ordering Information

- BGD 531/1 10-100 μ m (@10 μ m)
- BGD 531/2 20-200 μ m (@20 μ m)
- BGD 531/3 50-750 μ m (@25 μ m/@50 μ m)
- BGD 531/4 250-700 μ m (@50 μ m)
- BGD 531/5 50-950 μ m (@50 μ m)
- BGD 531/6 300-2600 μ m (Quadrilateral @25 μ m/@100 μ m)
- BGD 531/7 25-3,000 μ m (Hexagon)

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development