

## **Digital Dry Film Thickness Gauge - Ferro & Non Ferro - external probe: 0 -2,000 micron**

**BGD 546**

### **Product Description**

Tailored to specific application requirements, Solvica offers distinct types of thickness gauges that leverage the Hall effect and Eddy current principles. These gauges are designed to measure the thickness of non-ferromagnetic coatings on ferromagnetic metal substrates (iron, cobalt, nickel, and gadolinium) and the thickness of non-conductive coatings on non-magnetic metal substrates (copper, aluminum, magnesium, zinc, chromium, etc.).

The instrument finds wide applications in metal processing, coating, hardware, shipbuilding, aerospace, and other industries.

- Iron and aluminum dual use. Automatically identifies the substrate and facilitates fast automatic conversion (BGD 545 & BGD 546)
- Sensitive response with data measured in 0.5 seconds
- Simple design and compact size for easy portability and operation
- Ruby probe ensures abrasion and corrosion resistance, ensuring a long service life and minimizing errors due to wear
- Two units of  $\mu\text{m}/\text{mil}$  can be selected
- Advanced digital probe maintains a stable zero position for extended periods without drifting. Stable test data after multiple tests on the same position
- Unique algorithm ensures instrument linearity and measurement accuracy without the need for frequent calibration; only requires zero adjustment
- Good repeatability ensures compliance with Chinese national metrological testing inspection



### **Standards**

ISO 2178, ISO 2360, DIN/EN/ISO 2808, ASTM D1186, ASTM D1400, ASTM D7091, DIN 50981, DIN 50984, etc.

# Digital Dry Film Thickness Gauge - Ferro & Non Ferro - external probe: 0 -2,000 micron

**BGD 546**

## Main Technical Parameters

	BGD 545	<b>BGD 546</b>
Probe	Integrated probe	External cable probe
Substrate	Metal materials	
Measuring Range	0.0-2000µm	
Resolution	0.1µm (<100µm); 1µm (100µm-999µm); 10µm (>1000µm)	
Accuracy	≤±(3% reading + 2µm)	
Minimum Curvature	Convex: 5mm / Concave: 25mm	
Minimum Measuring Area	6mm <sup>2</sup>	
Minimum Substrate Thickness	Fe: 0.2mm / NFe: 0.05mm	
Display	128×48 dot matrix LCD	
Power Supply	2pcs of 1.5V AAA alkaline battery	
Dimension / Weight	101mm×62mm×28mm/79g (with battery)	

**Ordering information:** BGD 546 Digital Dry Film Thickness Gauge

## Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development