

## **Digital Stirrers**

# Precise Digital Overhead Stirrer: 160W/70L, LCD Display BGD 706

### **Product Description**

BGD 706 Precise Digital Stirrer (LCD display) with brushless motor. It can work under a high load for an extended period without any need for maintenance

Max. stirring capacity: 70L

Motor Rating Input/Output: 180W/160W

Timing Function: 0~99h, 59min (only available on BGD 706)

• Speed range: 50-1,100 rpm

• Display: LCD

Solvica's digital stirrers are of the highest quality. The core features a direct current brushless motor that is explosion-proof and addresses the shortcomings of traditional stirrers. These stirrers can operate under high loads for extended periods without requiring maintenance.



#### Features:

- High reliability and outstanding performance
- LCD display for precise monitoring of both set and actual speeds, with a wide speed range from 50 to 2200 rpm and control accuracy of ±3 rpm (BGD 702, BGD 704, BGD 706)
- Brushless DC motor for long life, maintenance-free operation, and explosion-proof performance. Torque trend display provides real-time information on viscosity changes
- Safety circuits ensure safe operation, with a stop function for anti-stall or overload conditions
- Smooth operation to prevent accidental spillage and splashing
- Maintains constant speed even with changes in sample viscosities
- Remote function for PC control and data transmission
- Auto-restart function available in case of power loss, enabling overnight operations



## **Digital Stirrers**

# Precise Digital Overhead Stirrer: 160W/70L, LCD Display BGD 706

## **Technical Specification**

| Model<br>Parameters            | BGD 701               | BGD 702 | BGD 703 | BGD 704 | BGD 706        |
|--------------------------------|-----------------------|---------|---------|---------|----------------|
| Max. Stirring Capacity (water) | 20                    | L       | 40 L    |         | 70 L           |
| Motor Rating Input             | 60 W                  |         | 120 W   |         | 180 W          |
| Motor Rating Output            | 50 W                  |         | 100 W   |         | 160 W          |
| Power                          | 70 W                  |         | 130 W   |         | 200 W          |
| Timing Function                | -                     |         |         |         | 0~99h<br>59min |
| Speed Range (rpm)              | 50-2,200              |         |         |         | 50-1,100       |
| Speed Display Accuracy (rpm)   | ±3                    |         |         |         | ±10            |
| Display                        | LED                   | LCD     | LED     | LCD     | LCD            |
| Voltage / Frequency            | 100 - 240V; 50Hz-60Hz |         |         |         |                |
| Max. Torque (N.cm)             | 40                    |         | 60      |         | 300            |
| Max. Viscosity (mPa.s)         | 10.000                |         | 50.000  |         | 100.000        |
| Chuck Range Diameter           | 0.5mm-10mm            |         |         |         |                |
| Dimension (WxHxD)              | 83 x 220 x 186 mm     |         |         |         |                |
| Weight (kg)                    | 2.4 2.8               |         | 3.2     |         |                |



### **Digital Stirrers**

# Precise Digital Overhead Stirrer: 160W/70L, LCD Display BGD 706

#### **Main Technical Parameters**

Packing List:

LCD digital overhead stirrer head: 1 pc
Flat Base: 1 pc (larger base optional)

Main Pole: 1 pc

• Dispersing pole with four leafs: 1 pc

### **Disclaimer**

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development