

High speed laboratory dissolver: Electric Lift, 2,200 W; 0-4,000r/min; Frequency Control

BGD 740-5

Product Description

BGD 740-5 High speed laboratory dissolver: Electric Lift, 2,200 W; 0-4,000 r/min; Frequency Control

We offer a wide range of high-speed dissolvers, applicable for dissolution and dispersion of coatings and inks, adhesives, latex and other chemical products.

With Siemens squirrel-cage motor of frequency control except BGD 740/1 and BGD 741/1 and frequency converter to adjust working speed and digital display. Low noise, big torque and wide adjustable speed. Stainless steel structure. Standard configuration: 2 or 4 (4 pcs only for 550W & 750W different dispersing blades and various options.



Technical Specification

- Siemens squirrel-cage motor of frequency control(except BGD 740/1 and BGD 741/1) and frequency converter to adjust working speed
- Digital display showing rotation speed
- Maintenance free motor without carbon brushes
- Low noise, high torque and wide adjustable speed
- Stainless steel structure
- Standard configuration: Two or four(only for 550W & 750W model) different dispersing blades, and optional sand-milling blades and stainless steel double jacket containers for milling.
- Models with 550W and 750W motor will be supplied with two additional extended shafts of dispersing blade 25mm & 45 mm for shorter container
- Overall size (mm) WxDxH (Low~Top): 700x720x1300~1510
- Power Supply: 220V 50Hz

High speed laboratory dissolver: Electric Lift, 2,200 W; 0-4,000r/min; Frequency Control

BGD 740-5

Main Technical Parameters

Model	Motor Power	Speed r/min	Max. Torque	Lift distance	Lift System	Dispersing blades
BGD 740/1	550W	0-7,500	1.91 N.m	240mm	Manual spring lift	50 & 60 mm
BGD 740/2	750W	0-6,000	2.87 N.m	240mm	Manual spring lift	50 & 60 mm
BGD 740/3	1,100W	0-6,000	3.82 N.m	320mm	Electric	60 & 80 mm
BGD 740/4	1,500W	0-5,000	5.73 N.m	320mm	Electric	80 & 100 mm
BGD 740/5	2,200W	0-4,000	7.64 N.m	520mm	Electric	100 & 120 mm
BGD 741/1	550W	0-7,500	1.91 N.m	300mm	Electric	50 & 60 mm
BGD 741/2	750W	0-6,000	2.87 N.m	300mm	Electric	50 & 60 mm
BGD 746	1,500W	100-20,000	1,6 N.m	300mm	Electric	50 & 60 mm

Accessoires

- BGD 1454 - Dispersing Container 5 L
- BGD 1455 - Dispersing Container 10 L

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development