

## **Water Bath 4.9L with 2 holes (Temperature Range: RT+5-99°C ; Power: 500W)**

**BGD 830**

### **Product Description**

---

Water and Oil Baths for laboratories, colleges and industrial enterprises for precise constant temperature and auxiliary heating.

The interior of the bath is constructed with stainless steel, and the center lids can be removed at your discretion

A high-precision microprocessor temperature controller ensures accurate and reliable temperature control

An audible and visible tracking alarm indicates over-temperature, providing reliable protection for samples



### **Technical Specification**

---

- The interior of the bath is constructed with smooth stainless steel
- Features a digit display, microprocessor control with a timing function
- Audible and visible tracking alarm indicates over-temperatures, providing reliable protection for samples
- Power supply: 220V/50Hz
- Temperature Stability:  $\pm 0.5^{\circ}\text{C}$
- Temperature Track Alarm:  $+2^{\circ}\text{C}$
- Timing Range: 1-9999 minutes

# Water Bath 4.9L with 2 holes (Temperature Range: RT+5-99°C ; Power: 500W)

**BGD 830**

## Main Technical Parameters

	Water Bath (with removable center lids)				Oil Bath	
	BGD 830	BGD 831	BGD 832	BGD 833	BGD 839	BGD 840
Power Supply	220V / 50Hz					
Input Power	500W	1000W	1500W	2000W	1000W	2000W
Temperature Range	From ambient +5-99°C				From ambient +5-200°C	
Temperature Stability	±0.5°C					
Tracking Alarm	±0.2°C					
Chamber Capacity	4.9L	9.9L	14.8L	19.8L	12L	20L
Interior Dimension (mm) WxDxH	150x300x110	300x300x110	450x300x110	600x300x110	250x250x200	400x250x200
Note	Two holes	Double columns - four holes	Double columes - six holes	Double Columns - eight holes	-	-

**Ordering information:** BGD 830 Waterbath Bath (4.9L)

## Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development