

#### **Heating Baths**

# Heating Bath: 11L Stainless Steel (RT+5-99°C)

### **Product Description**

BGD Series Heating Baths provide an economical solution for constant temperature and heating. These units are, widely utilized in material testing, quality control, and analysis



# **Technical Specification**

- The interior of the bath is made of smooth stainless steel
- Digital display, Microprocessor control with timing function
- Audible and visible alarm for tracking over-temperature conditions, providing reliable sample protection
- Temperature Stability: ±0.5°C
- Temperature Tracking Alarm: ±2°C
- Timing Range: 1 to 999 minutes



## **Heating Baths**

# Heating Bath: 11L Stainless Steel (RT+5-99°C)

#### **BGD 834**

#### **Main Technical Parameters**

Parameters:	
Temperature Range (°C)	RT~99
Volume (L)	11
Interior Dimension WxDxH (mm)	420×180×150
Overall Dimension WxDxH (mm)	570x270x260
Power (W)	500
Power Supply	220V / 50Hz

Ordering Information: BGD 834 - Heating Bath 11L

#### **Disclaimer**

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development