

## **LED UV Solidify Machine 395nm; 100x400mm**

**BGD 8400-B**

### **Product Description**

Compared to traditional ultraviolet (UV) solidifying machines that use mercury or gallium lamps as light sources, solidifying machines that use LED as a light source have several distinct advantages, including a longer lifetime, environmental friendliness (no ozone production), energy efficiency, and no significant heat emission during operation.

Currently, LED light sources with wavelengths of 365 nm and 395 nm are primarily used. At these wavelengths, the light emission intensity of LEDs is much higher than that of mercury lamps, which is beneficial for the deep curing of UV materials. At the same time, the heat generated by LED lighting is dissipated from the back, with no heat on the emitting side, thus avoiding any temperature effects on the curing materials.

Furthermore, LEDs emit narrow-bandwidth light, which allows for precise curing (including the precise curing of specific parts of materials, such as in 3D printing, or by adjusting the irradiation distance to achieve a specific degree of curing of the material).



## **LED UV Solidify Machine 395nm; 100x400mm**

### **BGD 8400-B**

#### **Technical Specification**

<b>Technical Items Ordering Information</b>	<b>BGD 8200/A</b>	<b>BGD 8200/B</b>	<b>BGD 8400/A</b>	<b>BGD 8400/B</b>
Wavelength	365 nm	395 nm	365 nm	395 nm
Lighting Size	100 mm × 200 mm	100 mm × 400 mm	100 mm × 200 mm	100 mm × 400 mm
Belt Width	200 mm (Teflon)	400 mm (Teflon)	200 mm (Teflon)	400 mm (Teflon)
Moving Speed	0.5 m/min ~ 8 m/min (adjustable)			
Irradiance Energy* (mW/cm <sup>2</sup> )	800 (UVA); 230 (UVV)	60 (UVA); 1200 (UVV)	800 (UVA); 230 (UVV)	60 (UVA); 1200 (UVV)
Adjustable Power	10% ~ 100% (knob type)			
Lighting Distance	10 mm ~ 100 mm (adjustable)			
LED Lifetime	20,000 h			
Heat Dissipation	Forced-air cooling			
Power Supply	AC 220 V, 50 & 60 Hz			
Total Power	500 W	1000 W	500 W	1000 W
Overall Size (L×W×H)	1000 × 410 × 660	1000 × 610 × 790	1000 × 410 × 660	1000 × 610 × 790
Remarks	* Data measured with UV Power Puck II (EIT, USA) at 20 mm distance. Peak ranges: UVA 320–390 nm; UVV 395–445 nm.			

## **LED UV Solidify Machine 395nm; 100x400mm**

**BGD 8400-B**

### **Main Technical Parameters**

---

**Ordering information:** BGD 8400/B - LED UV Solidify Machine 395 nm; 100x400mm

### **Disclaimer**

---

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development