

BGD 875 Continuous Condensation-water Climatic Chamber

BGD 875

Product Description

For some polymer materials used outdoors, enough experience indicates that corrosion caused by moisture (especially by condensation) is more serious than any other factor. So, testing coating film resistance to humidity is an important method to evaluate coating corrosion resistance.

BGD 875 Continuous Condensation-water Climatic Chamber offers a test condition for determining the resistance of paint films, paint systems and related products to conditions of condensation in accordance with the requirements of coating or product specifications.



Standards

ISO 6270 2007 series standards are test method standards which are used to evaluate the coatings film resistance to humidity, and consist of three parts as below:

- Part 1: Paints and varnishes -- Determination of resistance to humidity -- Part 1: Condensation (single-sided exposure)
- Part 2: Paints and varnishes -- Determination of resistance to humidity -- Part 2: Condensation (in-cabinet exposure with heated water reservoir)
- Part 3: Paints and varnishes -- Determination of resistance to humidity -- Part 2: Condensation (in-cabinet exposure with heated and bubble water reservoir)

Technical Specification

It is applicable to coatings, both on porous substrates such as wood, plaster and plasterboard and on non-porous substrates such as metal. It provides an indication of the performance likely to be obtained under severe conditions of exposure where continuous condensation occurs on the surface. The procedure can reveal failures of the coating (including blistering, staining, softening, wrinkling and embrittlement) and deterioration of the substrate.

BGD 875 Continuous Condensation-water Climatic Chamber

BGD 875

Main Technical Parameters

This tester is fast, easy to use and affordable. It uses 100% condensing humidity to simulate and accelerate damage caused by rain and dew on metals, paints, and organic materials. It accelerates over natural exposures by increasing moisture temperature. The tester replaces water immersion and ordinary (non-condensing) humidity tests.

- Operator can set three different working conditions humidification, natural cooling, dry and its corresponding temperature & running time. Any program including total test time and cycle times can be set freely.
- Automatic water supply
- Protector for water temperature ceiling
- The angle between test panel and the level: $(60^{\circ} \pm 5^{\circ})$
- Test Specimens Capacity: 40 pcs (150mm × 70mm standard size)
- Temperature Range of Working Room: RT~60°C (Dry or condensation)
- Overall Size: 1350 mm × 500 mm × 1100 mm (LxWxH)
- Weight: 130kg
- Power: 220V 50Hz ; Max. power of machine: 2.0 kW
- Ordering Information: BGD 875 - Continuous Condensation-water Climatic Chamber

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development