

Thermometers

Professional Thermocouple Thermometer (-50°C~1300°C)

BGD 948

Product Description

BGD 948 is a professional contact-type precise thermometer with white blacklight LCD, it has two channels K-type thermocouple to measure temperature. It's widely used in many fields needed to measure temperature.



Technical Specification

- Use K-type thermocouple to test temperature, resoluation can arrive 0.1
- With temperature compensation, ensure accuracy when measuring temperature
- Reading value can be converted /
- Auto. Power-off
- Hold max. value and hold test results
- Can change thermocouple



Thermometers

Professional Thermocouple Thermometer (-50°C~1300°C)

BGD 948

Main Technical Parameters

- Temperature Range -50~1300
- Accuracy ±1 ~±1.5
- Resolution 0.1
- Error ±0.5%±1
- Power Supply 9V battery work for 48 hours
- Size/Weight 165 ×76×43 mm/403g
- Accessories: 9V battery, Holster with stand, Type K temperature probe and gift box with carrying case.
- Ordering Information BGD 948: Professional Thermocouple Thermometer

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development