

Insulation Resistance Meter: 0-12x10¹² Ohm

BGD 968

Product Description

An insulation resistance meter is used to test electrician insulated materials, cable and wire, anti-static engineering and other electric materials.

It is made up of the most advanced high megohm resistance, weak current electronic components. With high precision, high resolution, strong capacity anti jamming etc characters.



Technical Specification

- Rated voltage: 10V 100V 500VΩ
- Measuring Scope 0-2x10¹²Ω
- Measurement error
 - ± 1% showing value+2 LSD $R \leq 10^9 \Omega$
 - ± 3% showing value+2 LSD $10^9 \sim 10^{10} \Omega$
 - ± 5% showing value+2 LSD $10^{10} \sim 10^{12} \Omega$
 - ± 10% showing value+2LSD $10^{12} \sim 10^{14} \Omega$
 - ± 20% showing value+10 LSD $> 10^{14} \Omega$
- Testing set time 1min~7min
- Power supply: 8 pcs 1.2V (rechargeable batteries) or 8 pcs 1.5V battery
- Operating environment: 0~40°C 85%RH (25°C)
- Weight: 2kg
- Size: 270mm×250mm×100mm

Insulation Resistance Meter: 0-12x10¹² Ohm

BGD 968

Main Technical Parameters

- Ordering Information BGD 968 - Insulation Resistance Meter

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development