

## **BGD DGA-SQR1 - U-shaped Double Gap Applicator: 225**

**µm - 350 µm**

**BGD DGA-SERIES**

### **Product Description**

---

The double bar film applicator has two gap clearances. The U Bar design channels the coating for an accurate film width.

- Large selection of film widths
- Stainless steel construction for long life
- Produced on request with customer-specific requirements.



### **Technical Specification**

---

Produced on request with tailor-made theoretical wet film thickness.

Please contact us to discuss your specific requirements and specification.

## **BGD DGA-SQR1 - U-shaped Double Gap Applicator: 225**

**µm - 350 µm**

**BGD DGA-SERIES**

### **Main Technical Parameters**

---

Ordering information: BGD DGA U-shaped Double Gap Applicators

### **Disclaimer**

---

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development