

Cone & Plate Viscometer Spindle CAP-Spindles 1-6

CAP-SERIES 1-6

Product Description

Cone & Plate Viscometer - Spindles 1-6



Technical Specification

Ordering Information Parameters	BGD 159/2 (750 RPM)(-1 ~150)	BGD 159/3 900 RPM (-1 ~150)
Cone No.: CAP-01 Shear Rate: 13.3N Sample Volume: 67μL	25-250 mPa.s	20-200 mPa.s
Cone No.: CAP-02 Shear Rate: 13.3N Sample Volume: 38μL	50-500 mPa.s	40-400 mPa.s

Cone & Plate Viscometer Spindle CAP-Spindles 1-6

CAP-SERIES 1-6

Cone No.: CAP-03 Shear Rate: 13.3N Sample Volume: 24µL	100-1,000 mPa.s	200-2,000 mPa.s
Cone No.: CAP-04 Shear Rate: 3.3N Sample Volume: 134µL	200-2,000 mPa.s	400-4,000 mPa.s
Cone No.: CAP-05 Shear Rate: 3.3N Sample Volume: 67µL	400-4,000 mPa.s	300-3,000 mPa.s
Cone No.: CAP-06 Shear Rate: 3.3N Sample Volume: 30µL	1,000-10,000 mPa.s	800-8,300 mPa.s

Cone & Plate Viscometer Spindle CAP-Spindles 1-6

CAP-SERIES 1-6

Accessoires

- CAP-01 - Cone & Plate Viscometer Spindle CAP-01
- CAP-02 - Cone & Plate Viscometer Spindle CAP-02
- CAP-03 - Cone & Plate Viscometer Spindle CAP-03
- CAP-04 - Cone & Plate Viscometer Spindle CAP-04
- CAP-05 - Cone & Plate Viscometer Spindle CAP-05
- CAP-06 - Cone & Plate Viscometer Spindle CAP-06

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development