
Fast Moisture Tester: IR heating; 110g/0.01g

MB 23ZH

Product Description

Introducing our new Moisture Analyzers, tailored for precise moisture analysis in routine applications. Engineered with durability and precision in mind, these analyzers boast a sleek, compact design, delivering dependable and accurate results across a wide spectrum of moisture analysis tasks.

Key Features:

- **Generous Capacity:** Choose between a 110-gram or 90-gram capacity, making it suitable for diverse fields such as food, agriculture, chemical, and pharmaceutical industries, requiring measurements up to 0.01% (0.001g)
- **User-Friendly Operation:** Setting up and operating the analyzer is effortless. Simply press and hold buttons to configure drying parameters, catering to operators of all proficiency levels, perfect for routine tasks.
- **Space-Saving Design:** The compact footprint ensures minimal space consumption, fitting seamlessly into any workspace
- **Effortless Maintenance:** The easy-to-clean heating chamber facilitates frequent use and ensures cost-effective maintenance, enhancing longevity and efficiency



Upgrade your moisture analysis experience with our innovative Moisture Analyzers, where precision meets simplicity.

Technical Specification

Fast Moisture Tester: IR heating; 110g/0.01g

MB 23ZH

Technical Parameters	MB 23ZH	MB 25ZH	MB 27ZH
Capacity	0.3% (3g sample)	0.2% (3g sample)	0.2% (3g sample)
	0.2% (10g sample)	0.05% (10g sample)	0.05% (10g sample)
Readability	0.1%/0.01g	0.05%/0.005g	0.01%/0.001g
Sample Size	3g to 20g typical, 0.5g min.		
Interface	Bidirectional RS-232		
Timer	1-99 minutes, 30-second increments to 60 minutes		
Heating Technology	Infrared (no glass)	Halogen	
Temperature Range	50°C to 160°C in 5°C increments		
Power	100 to 240 VAC, 50/60Hz		
Tare Range	To capacity by subtraction		
Operating Temperature Range	5°C to 40°C		
Display Type	Custom backlit LCD		
Displays	% moisture or % solids or weight (g), temperature, time		
Pan Size (diameter)	90 mm		
Dimensions (WxHxD)	17cmx13cmx28cm		17cmx14cmx28cm
Net Weight	2.1 kg		
Shipping Weight	3.9 kg		

Fast Moisture Tester: IR heating; 110g/0.01g

MB 23ZH

Main Technical Parameters

Ordering information: MB 23 ZH Fast Moisture Tester

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development