

## Low Temp. Thermostatic Bath: -5~100°C ; 7,5L

**THD-0506**

### Product Description

---

THD Series Low Temperature Thermostatic Baths for general purpose.

Temperature controlled by microprocessor with PID regulator. Fastness in temperature rising and dropping, and high precision in controlling of temperatures. Both vertical as horizontal (W) models. Volumes: 6-30 liters.



Vertical



Horizontal

### Technical Specification

---

- Range of temperature (°C): -5-100
- Fluctuating degree of temperature (°C):  $\pm 0.05$
- Size of inner container (mm): 250 x 200 x 150
- Volume of inner container (L): 7.5
- Size of opening (mm): 180 x 150
- Depth (mm): 150
- Pump flow: (L/min): 6
- Model: Vertical

## Low Temp. Thermostatic Bath: -5~100°C ; 7,5L

**THD-0506**

### Main Technical Parameters

Technical Item Model	Range of temperature (°C)	Fluctuating degree of temperature (°C)	Size of inner container (mm)	Volume of inner container (mm)	Size of opening (mm)	Depth (mm)	Pump flux (L/m)
<b>THD-0506</b>	-5 100	±0.05	250×200×150	7.5 L	180×150	150	6

### Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development